

H2 5-12kW Low Voltage Hybrid Inverter

SAJ's Low Voltage solution of hybrid inverter, allow to be compatible with both LFP and Lead-Acid Battery, support storing energy from diesel generator, provide a most cost efficiency solution for those entry-level market. H2 covers 5-12kW, 2MPPTs, single phase grid.



- ❑ Max 20A input current to better match high power panel
- ❑ 200% DC oversizing
- ❑ Built-in meter zero export limiter
- ❑ Max. 4 pcs parallel for on-grid and off-grid operation
- ❑ Heat-resistant (> 50°C with derating)
- ❑ Support generator / smart load access

H2-5K-LS2 | H2-6K-LS2 | H2-7.6K-LS2
H2-8K-LS2 | H2-10K-LS2 | H2-12K-LS2

MODEL	H2-5K-LS2	H2-6K-LS2	H2-7.6K-LS2	H2-8K-LS2	H2-10K-LS2	H2-12K-LS2
DC Input						
Max. PV Array Power [Wp]@STC	10000	12000	15200	16000	20000	24000
Max. DC Voltage [V]	500					
MPPT Voltage Range [V]	90 ~ 480					
Rated DC Voltage [V]	360					
Start Voltage [V]	80					
Max. DC Input Current [A]	20/20				40/40	
Max. DC Short Circuit Current [A]	25/25				50/50	
No. of MPPT	2					
Battery Parameters						
Battery Type	Lead-acid or LiFePO4					
Battery Voltage Range [V]	40 ~ 60					
Max. Charging/Discharging Current [A]	100	120	190	190	240	
AC Output [On-grid]						
Rated AC Power [W]	5000	6000	7600	8000	10000	12000
Max. Apparent Power [VA]	5500	6600	8360	8800	10000	12000
Rated Output Current [A]@230Vac	21.8	26	33	34.8	43.5	52.2
Max. Output Current [A]	25	30	38	40	45.5	54.6
Rated AC Voltage/Range [V]	L+N+PE, 220,230,240/180 ~ 280					
Rated Output Frequency/Range [Hz]	50,60/45 ~ 55,55 ~ 65					
Power Factor [cos φ]	0.8 leading ~ 0.8 lagging					
Total Harmonic Distortion [THDi]	<3%					
AC Input [On-grid]						
Rated AC Voltage/Range [V]	L+N+PE, 220,230,240/180 ~ 280					
Rated Input Frequency [Hz]	50,60					
Max. Input Current [A]@230Vac	50	60	76	80	91	100
AC Output [Back-up]						
Max. Output Power [VA]	5000	6000	7600	8000	10000	12000
Max. Output Current [A]	25	30	38	40	45.5	54.6
Peak Output Apparent Power [VA]	6000,60s	7200,60s	9120,60s	9600,60s	12000,60s	13200,60s
Rated AC Voltage/Range [V]	L+N+PE, 220,230,240/180 ~ 280					
Rated Output Frequency/Range [Hz]	50,60/45 ~ 55,55 ~ 65					
Output THDv (@ Linear Load)	<3%					
Efficiency						
Max. Efficiency	97.6%					
Euro Efficiency	97.0%					
Protection						
Battery Input Reverse Polarity Protection	Integrated					
Over load Protection	Integrated					
AC Short Circuit Current Protection	Integrated					
DC Surge Protection	Integrated					
AC Surge Protection	Integrated					
Anti-islanding Protection	Integrated					
AFCI Protection	Optional					
RSD Protection	Optional					
Interface						
PV Connection	Terminal Block					
AC Connection	Terminal Block					
Battery Connection	Terminal Block					
Display	LED+APP					
Communication	Wi-Fi/Ethernet/4G(Optional)					
General Parameters						
Topology	Non-isolated					
Operating Temperature Range	-40°C to +60°C (50°C to 60°C with derating)					
Cooling Method	Intelligent Fan cooling					
Ambient Humidity	0-100% Non-condensing					
Altitude	4000m (>3000m Power Derating)					
Noise [dBA]	<50					
Ingress Protection	IP65					
Dimensions [H*W*D] [mm]	590*380*241					
Weight [kg]	29					
Warranty [Year]	5/10					
Standard	EN 62109-1/2, EN 61000-6-1/2/3/4, IEC 62116, IEC 61727, IEC62183, PEA&MEA, NBR 16149, NBR 16150, PORTARIA N° 140,515, NRS097					